

AMENDMENTS TO THE CLAIMS

1. (Canceled)
2. (Currently Amended) A method for controlling a flow of information, comprising:
receiving, at a base station, [[a]] at least two signals from at least two user equipment,
each signal requesting to transmit information from the corresponding user
equipment to the base station;
determining at least one relative delay between signals transmitted by said at least two
user equipment;
determining a time at which the information is permitted to be transmitted by each of said
at least two user equipment based on the relative_delay; [[and]]
transmitting [[a]] signals to each of said at least two user equipment, each signal
identifying a time at which information is permitted to be transmitted from the
corresponding user equipment to the base station; and
transmitting a synchronizing signal, and wherein transmitting a signal identifying the
time at which information is permitted to be transmitted further comprises
transmitting a signal identifying the time as a function of the synchronizing signal
at which information is permitted to be transmitted.
3. (Canceled)

4. (Currently Amended) A method, as set forth in claim ~~[[3]]~~ 2, wherein:
transmitting the signal identifying the time as a function of the synchronizing signal at which information is permitted to be transmitted further comprises transmitting over a shared channel the signal identifying the time as a function of the synchronizing signal at which information is permitted to be transmitted.
5. (Original) A method, as set forth in claim 2, wherein transmitting a signal identifying the time at which information is permitted to be transmitted further comprises transmitting a signal identifying a frame in which information is permitted to be transmitted.
6. (Currently Amended) A method, as set forth in claim 2, wherein determining at least one relative delay between signals transmitted by said at least two user equipment further comprises determining a propagation delay between signals transmitted by said at least two user equipment.
7. (Currently Amended) A method, as set forth in claim 2, wherein determining at least one relative delay between signals transmitted by said at least two user equipment further comprises determining a processing delay between signals transmitted by said at least two user equipment.
8. (Previously Presented) A method, as set forth in claim 2, further comprising:
receiving the information at a first preselected time;

comparing the first preselected time with the identified time to determine the relative delay between at least two user equipment.

9. (Currently Amended) A method for controlling a flow of information from a user to a base station, comprising:
receiving a signal from the user requesting to transmit information to the base station;
determining at least one relative delay between signals transmitted to the base station by
the user and at least one other user;
determining a time at which the user is to transmit the information to the base station,
wherein the determined time is a function of the relative delay; [[and]]
transmitting a signal to the user identifying the time at which information is permitted to
be transmitted; and
transmitting a synchronizing signal to the user, wherein transmitting a signal identifying
the time at which information is to be transmitted further comprises transmitting a
signal identifying the time as a function of the synchronizing signal at which
information is permitted to be transmitted.
10. (Canceled)
11. (Currently Amended) A method, as set forth in claim [[10]] 9, wherein:
transmitting the signal identifying the time as a function of the synchronizing signal at
which information is to be transmitted further comprises transmitting over a

shared channel the signal identifying the time as a function of the synchronizing signal at which information is to be transmitted.

12. (Currently Amended) A method, as set forth in claim [[10]] 9, further comprising a plurality of users, and wherein:
transmitting the synchronizing signal further comprises transmitting the synchronizing signal over a shared channel to each of the plurality of users; and
transmitting the signal identifying the time as a function of the synchronizing signal at which information is to be transmitted further comprises transmitting over the shared channel to the plurality of users a signal identifying a unique time, as a function of the synchronizing signal, at which information is to be transmitted.
13. (Original) A method, as set forth in claim 9, wherein transmitting a signal identifying the time at which information is to be transmitted further comprises transmitting a signal identifying a frame in which information is to be transmitted.
14. (Currently Amended) A method, as set forth in claim 9, wherein determining at least one relative delay between signals transmitted to the base station by the user and at least one other user further comprises determining a propagation delay associated with signals delivered by the user.
15. (Currently Amended) A method, as set forth in claim 9, wherein determining at least one relative delay between signals transmitted to the base station by the user and at least one

other user further comprises determining a processing delay associated with signals delivered by the user.

16. (Currently Amended) An apparatus, comprising:

means for receiving, at a base station, [[a]] at least two signals from at least two user equipment, each signal requesting to transmit information from the corresponding user equipment to the base station;

means for determining at least one relative delay between signals transmitted by said at least two user equipment;

means for determining a time at which the information is permitted to be transmitted by each of said at least two user equipment based on the relative_delay; [[and]]

means for transmitting [[a]] signals to each of said at least two user equipment, each signal identifying a time at which information is permitted to be transmitted from the corresponding user equipment to the base station; and

means for transmitting a synchronizing signal to the user, wherein transmitting a signal identifying the time at which information is to be transmitted further comprises transmitting a signal identifying the time as a function of the synchronizing signal at which information is permitted to be transmitted.

17. (Currently Amended) A method for controlling the flow of information between a user and a base station, comprising:

transmitting a signal from the user requesting permission from the base station to transmit information;

determining at least one relative delay between signals transmitted to the base station by
the user and at least one other user;

determining a time at which the user is to transmit the information to the base station,
wherein the determined time is a function of the relative delay; [[and]]

transmitting a signal to the user identifying the time at which information is permitted to
be transmitted;

transmitting a synchronizing signal to the user, wherein transmitting a signal identifying
the time at which information is to be transmitted further comprises transmitting a
signal identifying the time as a function of the synchronizing signal at which
information is permitted to be transmitted; and

transmitting the information from the user to the base station at the identified time.

18. (Previously Presented) A method, as set forth in claim 17, further comprising:

receiving the information from the user at a first preselected time;

comparing the first preselected time with the identified time to determine the relative
delay between the user and at least one other user.

19. (Currently Amended) A method for controlling the flow of information between a user
and a base station, comprising:

receiving, at the user, a synchronizing signal from the base station;

transmitting a signal from the user requesting permission from the base station to transmit
information;

receiving a signal from the base station identifying a time relative to the synchronizing signal at which information is to be transmitted, the time being determined based on a relative delay between signals transmitted to the base station by the user and at least one other user; and
transmitting the information from the user to the base station at the identified time.

20. (Original) A method, as set forth in claim 19, wherein:

receiving a signal from the base station identifying the time at which information is to be transmitted further comprises receiving a signal from the base station identifying a substantially unique time at which information is to be transmitted.

21. (Original) A method, as set forth in claim 19, wherein:

receiving a signal from the base station identifying the time at which information is to be transmitted further comprises receiving a signal from the base station identifying a substantially unique frame associated with the synchronizing signal during which information is to be transmitted.

22. (Original) A method, as set forth in claim 19, wherein:

receiving a synchronizing signal from the base station further comprises receiving a synchronizing signal from the base station over a shared channel.